

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924
International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: CERAMIC EXTREME BRAKE PARTS LUBRICANT 8 FL.OZ
Item No: 24125
Product Type: Lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
SYNTHETIC BASE OILS Mixture	>85	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.
Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness..

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting skin disorders.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Obtain medical attention immediately..
Inhalation: If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.
Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): >500 degrees F. Method: COC
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Treat as oil fire. Firefighters should wear self-contained breathing apparatus.
Hazardous Products of Combustion: Oxides of carbon
Unusual Fire/Explosion Hazards: None.
Lower Explosive Limit: Not determined.
Upper Explosive Limit: Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Keep in cool and dark place. Avoid direct sunlight
Handling: Good hygienic practices should be observed. Work clothes should be washed separately at the end of each work day. Disposable clothing should be discarded with material. Discard contaminated leather gloves and shoes. Spills may cause slippery floors. Proper footwear required.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses or goggles.
Skin: Neoprene or nitrile gloves recommended..
Ventilation: General ventilation is usually adequate
Respiratory Protection: Not normally necessary.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Purple semi-solid
Odor:	MILD
Boiling Point:	Not determined.
pH:	Does not apply
Solubility in Water:	Insoluble
Specific Gravity:	0.89
VOC Content(Wt.%):	None
Vapor Pressure:	Not Determined
Vapor Density (Air=1):	> 1 (air = 1)
Evaporation Rate:	<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at normal conditions
Hazardous Polymerization:	WILL NOT OCCUR
Incompatibilities:	Strong oxidizers
Conditions to Avoid:	Welding.
Hazardous Products of Combustion:	Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name:	Unrestricted
Hazard Class:	None
UN/ID Number:	None
Marine Pollutant:	None

IATA

Proper Shipping Name:	Unrestricted
Class or Division:	None
UN/NA Number:	None

IMDG

Proper Shipping:	Unrestricted
Hazard Class:	None
UN Number:	None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

Product name: CERAMIC EXTREME BRAKE PARTS
LUBRICANT 8 FL.OZ

Item No: 24125

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, INSTABILITY 1

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager

Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: 05/23/2006

Revision 1

Number: