


MATERIAL SAFETY DATA SHEET

Product: LUBEGARD® Gear Fluid Supplement

Stock Number	Size	NFPA Rating
30903	8 oz	0-Insignificant
70902	32 oz	1-Slight
70904	5 gal	2-Moderate
		3-High
		4-Extreme



SECTION I. MANUFACTURER AND LOCATION

Manufacturer: International Lubricants, Inc.
Location: P.O. Box 24743, Seattle, WA 98124-0743
Telephone: (206) 7625-5343
Emergency Contact: CHEMTEL, (800) 255-3924

SECTION II. MATERIAL IDENTIFICATION AND INFORMATION

COMPONENT	CAS NUMBER	TLV/PEL (MG/M ³)	VOLUME %
Solvent Refined Paraffinic Petroleum Base Stock	64742-55-8	5	60
Phosphite Adduct of Vegetable Oil	135458-00-3	NE	>15

The specific chemical name and composition of the components not disclosed is confidential business information and is withheld as permitted by 29CFR 1910.1200 and various state Right-to-Know laws.

SECTION III HAZARDS INFORMATION

Prolonged contact may cause skin irritation.

Potential Health Effects:

Eyes: May cause irritation or discomfort.

Skin Contact: None expected. However, repeated contact may cause irritation or dermatitis.

Inhalation: Negligible unless heated to produce vapors. Vapors may cause irritation, dizziness and nausea.

Ingestion: May result in vomiting. Aspiration of liquid into lungs may cause severe lung injury.

Carcinogenicity NTP: No IARC: No OSHA: No

Chronic Overexposure: Prolong exposure may cause skin irritation or dermatitis. Pre-existing skin or eye disorder may become aggravated.

Medical conditions aggravated by exposure: Pre-existing skin, eye or respiratory disorder.

SECTION IV. FIRST AID

Contact with EYES: Immediately flush with large quantities of cool water for at least 15 minutes. Get medical attention if irritation persists.

Contact with SKIN: Wash off with soap and water. Get medical attention if irritation persists.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

Ingestion: Do not induce vomiting. Get emergency medical attention.

SECTION V. FIRE AND EXPLOSION DATA

Flashpoint (Cleveland Open Cup): < 370°F
Auto Ignition Temperature: NE
Flammable Limits: NE

Hazardous Thermal Decomposition: When burning could release toxic carbon monoxide, sulphur dioxide or oxides of phosphorous and nitrogen.

Fire Extinguishing Agents: Water spray (fog), dry chemical, foam, halon, or CO₂. Water stream may splash burning liquid and spread fire.

Unusual Fire and Explosion Hazards: Slight fire hazard when heated above 370°F. Vapors can burn when exposed to sources of ignition, such as open flame or spark. Vapors could possibly explode if ignited in confined space.

Special Fire Fighting Procedures: As for petroleum products. Do not use direct or heavy water stream to fight fire. Use self contained breathing apparatus to fight fires.

HMIS:	Health: 1	Flammability: 1	Reactivity: 0	PPE: B
NFPA:	Health: 1	Flammability: 1	Reactivity: 0	

SECTION VI. ACCIDENTAL RELEASE MEASURE

Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

SECTION VII. STORAGE AND HANDLING

Keep containers sealed until ready to use. Maximum storage temperature: 120°F. Store in well ventilated areas. Store in cool, dry ventilated area and away from sources of ignition.

SECTION VIII. EXPOSURE CONTROL / PERSONAL PROTECTION

Ventilation (Local, Mechanical, Special):	Use in a well ventilated area with local exhaust ventilation.
Respiratory Protection:	None required in normal use. Use only NIOSH/MSHA
Gloves:	Not required in normal use.
Eye Protection:	Goggles or safety glasses are recommended.
Other Protective Equipment:	Practice good personal hygiene. Wash hands after using and handling.

SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name:	Mixture
Form:	Amber brown oily liquid
Odor:	Slightly oily odor
Specific Gravity (Water = 1.00):	0.8498
Melting Point:	NA
Boiling Point:	NA
Volatility, weight % at 25°C:	NIL
Evaporation Rate:	Less than butylacetate (1)
Vapor Pressure, mmHg at 25°C:	< 0.1
Vapor Density (Air = 1):	Heavier than air
Solubility in Water:	Insoluble
Stability:	Very stable under normal conditions
Weight Per Gallon:	7.076

SECTION X. REACTIVITY

Reactivity:	Stable under normal temperatures and pressures.
Incompatibilities:	Strong oxidizing agents, heat, open flame.
Hazardous Polymerization:	Has not been known to occur.
Hazardous Decomposition Products:	When burning could release carbon monoxide, sulphur dioxide, or oxides of phosphorous.

SECTION XI. TOXICOLOGICAL INFORMATION

Long term toxicological studies have not been conducted. See section 3 for chronic overexposure and carcinogenicity.

SECTION XII. ECOLOGICAL INFORMATION

Ecotoxicity: No data available.

Environmental Fate: No data available.

SECTION XIII. Waste Disposal

Dispose all used and unused product in accordance with federal, state, and local regulations. Contact state or local agency for specific rules. Do not dump into sewer, on the ground or in to water

SECTION XIV. TRANSPORTATION (Ground)

D.O.T. Shipping Name:	Not Regulated
D.O.T. ID Number:	NA
Reportable Quantity:	NA
Special Transportation Notes:	None

SECTION XV. REGULATORY INFORMATION

TSCA: All components are either listed or exempt.
SARA Title III Section 311/312: NA
Section 313: NA
CERCLA: NA
Extremely hazardous substance: NA
California prop 65: NA

SECTION XVI. OTHER INFORMATION

Notes: NA = Not Applicable
NE = Not Established
ND = Not Determined

International Lubricants, Inc. believes that the information and recommendations contained herein (including data and statements) good faith but makes no representation as to its comprehensiveness or accuracy. No warranty of fitness, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and of the information referred to herein are beyond the control of International Lubricants, Inc., International Lubricants, Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

Prepared By: Kevin Vyas

Origin Date: 11/01/87
Revision Date: 01/06/03
Supersedes: 10/01/99